

Chemola™ Desco 1055

Premium Synthetic Valve Lubricant

Chemola™ Desco 1055 is a state-of-the-art synthetic lubricant that is exceedingly resistant to hydrocarbons, water and hydrochloric acid. Chemola™ Desco 1055 is formulated with solid lubricants to provide lubrication to 600°F.

Recommended Uses

Frac applications, condensate, aliphatic hydrocarbons, butane, diesel fuel, hot asphalt, hot gases, hot oil, LPG, natural gas, sour gas and oil, low to moderate levels of hydrogen sulfide and/or carbon dioxide.

Typical Characteristics

Appearance	Silver-black, smooth, tacky	
NLGI	1.5 - 2	
Penetration (ASTM D217)	280-310	
Worked Penetration, 60x (ASTM D217)	280-310	
Base Oil	Synthetic ester blend	
Base Oil Viscosity	10,000 cSt at 40°C	
Base Oil Pour Point	-15°F (-9°C)	
Thickener	Inorganic	
Additives	Antioxidant package	
Solids Content	Molydisulfide, natural minerals	
Dropping Point (ASTM D566)	>500°F (260°C)	
Flash Point	>450°F (232°C)	
Temperature Range	-40°F to 600°F (-40°C to 316°C)	
Storage Stability (50°C, 120 days)	Pass	
Resistance to Water (FTM 5415)	Pass	
Resistance to 50% Ethanol in Water (FTM5415)	Pass	
Resistance to Synthetic Condensate (FTM 5415 mod)	Pass	
Resistance to Mineral Spirits (FTM 5415 mod)	Pass	
Resistance to 20% Hexane in Mineral Spirits (FTM 5415 mod)	Pass	
Resistance to Diesel Fuel (FTM 5415 mod)	Pass	
Resistance to HCl(aq)	Pass	
Resistance to Brine, 135°F (53°C) (ASTM D1748 mod)	Pass	

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com





Chemola™ Desco 1055

Premium Synthetic Valve Lubricant

Packaging Information

Part Number	Item Number	Unit Size	Quantity
10551-01-IA	0887010QB	10 lb can	
1055J-01-IA	0887016JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
10552-01-IA	0887020BM	20 lb pail	
10554-01-IA	0887040BM	40 lb pail	
10510-01-IA	0887120KG	120 lb keg	
1055K-01-IA	088712KBX	"K" stick 1-1/2" x 10-1/2"	12 per box
10540-01-IA	0887400DL	400 lb drum with liner	

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.

Special packaging sizing available upon request.



P.O. Box 450109 Houston, Texas 77245 www.socousa.com Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



