

Chemola TM Desco 750 High Temperature Hydrocarbon Service

Chemola™ Desco 750 is formulated with 100% synthetic oils and contains solid lubricants for effective lubrication at temperatures to 900°F.

Recommended Uses

ChemolaTM Desco 750 can be used in aliphatic hydrocarbons, asphalt, hot oil, lubricating oils and steam.

Typical Characteristics

Appearance	Black, smooth, tacky	
NLGI	3	
Penetration (ASTM D217)	225-255	
Worked Penetration, 60x (ASTM D217)	225-255	
Base Oil	Synthetic and natural ester	
Base Oil Viscosity	500 cSt at 40°C	
Base Oil Pour Point	-4°F (-16°C)	
Thickener	Inorganic	
Additives	Antioxidant package	
Solids Content	Graphite	
Specific Gravity	1.0	
Density (lb/gal)	8.6	
Dropping Point (ASTM D566)	>500°F (260°C)	
Flash Point	>550°F (288°C)	
Temperature Range	-20°F to 900°F (-29°C to 482°C)	
Storage Stability	Pass	
Resistance to Water (FTM 5415)	Pass	
Resistance to Mineral Spirits (FTM 5415 mod)	Pass	
Resistance to HCl(aq)	Pass	

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.

Special packaging sizing available upon request.









ChemolaTM Desco 750 High Temperature Hydrocarbon Service

Packaging Information

Part Number	Item Number	Unit Size	Quantity
750B-01-IA	082072BBX	"B" stick 3/8" x 1-1/2"	72 per box
750C-01-IA	082032CBX	"C" stick 7/16" x 2-1/8"	32 per box
750D-01-IA	082028DBX	"D" stick 1/2" x 2-1/4"	28 per box
750G-01-IA	082014GBX	"G" stick 5/8" x 3-1/2"	14 per box
750J-01-IA	082016JBX	"J" stick 1-3/8" x 8-1/2"	16 per box
750K-01-IA	082012KBX	"K" stick 1-1/2" x 10-1/2"	12 per box
750Z-01-IA	0820010CR	14 oz cartridge	10 per carton
7501-01-IA	0820010QB	10 lb can	
7502-01-IA	0820020BM	20 lb pail	
7504-01-IA	0820040BM	40 lb pail	
7510-01-IA	0820120KG	120 lb keg	
7540-01-IA	0820400DR	400 lb drum	

*FOR USE IN GATE, BALL AND PLUG VALVES.

DO NOT USE ON OXYGEN SERVICE.

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



