



# Chemola™ Desco 960

## Body Fill

**Chemola™ Desco 960** is formulated for valves that contain body cavities. It is an economical body fill that will displace water and other containments. Chemola™ Desco 960 has high metal adhesion to lubricate and seal gates as they enter the body cavity.

### Recommended Uses

Chemola™ Desco 960 is excellent for use in lubricating valves after hydrostatic testing for storage or shipping.

Appearance	Gray, smooth
NLGI	2
Penetration (ASTM D217)	255-265
Worked Penetration, 60x (ASTM D217)	255-265
Base Oil	Mineral oil
Base Oil Viscosity	145 cSt at 40°C
Base Oil Pour Point	-10°F (-23°C)
Thickener	Inorganic
Additives	Antioxidant/corrosion inhibitor package
Solids Content	Graphite
Specific Gravity	0.9
Density (lb/gal)	7.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>400°F (204°C)
Temperature Range	-10°F to 350°F (-23°C to 177°C)

### Packaging Information

Part Number	Item Number	Unit Size
960Z-01-IA	0114010CR	14 oz cartridge
601-01-IA	0114010CN	10 lb can
9602-01-IA	0114020BM	20 lb pail
9604-01-IA	0114035BM	35 lb pail
9610-01-IA	0114120KG	120 lb keg
9640-01-IA	0114400DR	400 lb drum

**DO NOT USE ON OXYGEN SERVICE.**  
*Special packaging sizing available upon request.*

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
 Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

Premium