



# Chemola™ Desco Marine Grease

## Lubrication Protection in Wet Environments

**Chemola™ Desco Marine Grease** is a product designed and formulated to offer superior lubrication protection in wet environments. It offers protection from corrosion and promotes water resistance. It is useful for all marine environments, both fresh and salt water, and offers complete lubrication under the most rigorous conditions.

### Recommended Uses

Ball joints control cables, slides, shafts, gearing, knuckles and other marine applications exposed to salt or fresh water corrosion

### Typical Characteristics

Appearance	Green, tacky, smooth
NLGI	4
Penetration (ASTM D217)	170-190
Worked Penetration, 60x (ASTM D217)	170-190
Base Oil	Synthetic hydrocarbon blend
Base Oil Viscosity	630 cSt at 100°C
Base Oil Viscosity Index	173
Base Oil Pour Point	5°F (-15°C)
Thickener	Inorganic
Additives	Rust and corrosion inhibitors
Specific Gravity	1.0
Density (lb/gal)	8.0
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>400°F (200°C)
Temperature Range	0°F to 400°F (-18°C to 204°C)
Army-Navy Humidity Test AN-H-31	Pass

### Packaging Information

Part Number	Item Number	Unit Size	Quantity
210Z-04-1A	0121010CR	14 oz cartridge	10 per case
	0121010BP	10 lb pail	
2103-04-1A	0121035BP	35 lb pail	
	0121120KG	120 lb keg	
	0121400DR	400 lb drum	

**DO NOT USE ON OXYGEN SERVICE.**  
*Special packaging sizing available upon request.*

**SOUTH COAST PRODUCTS**

P.O. Box 450109 Houston, Texas 77245 [www.socousa.com](http://www.socousa.com)  
 Tel: (713) 225-0048 (800) 535-5823 [custserv@socousa.com](mailto:custserv@socousa.com)

**Premium**