



Chemola™ Desco Red Bentone

High Temp Grease

Chemola™ Desco Red Bentone offers the ultimate in general purpose lubrication with the added property of extreme pressure lubricity. This grease is compounded from a blend of the finest mineral and synthetic oils coupled with an inorganic gelling agent. Chemola™ Desco Red Bentone Grease offers additional protection to meet today’s high performance requirements.

Recommended Uses

King pin, ball joints, bearings, slides, gears, universal joints and screws. Excellent for use on high speed bearings.

Typical Characteristics

Appearance	Red, tacky, smooth
NLGI	3
Penetration (ASTM D217)	245-255
Worked Penetration, 60x (ASTM D217)	245-255
Base Oil	Mineral oil
Base Oil Viscosity	143 cSt at 100°C
Base Oil Viscosity	11 cSt at 40°C
Base Oil Viscosity Index	40
Base Oil Pour Point	-10°F (-23°C)
Thickener	Inorganic
Additives	EP, antioxidant and corrosion inhibitors
Specific Gravity	0.9
Density (lb/gal)	7.5
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>400°F (200°C)
Temperature Range	0°F to 450°F (-18°C to 232°C)
Four-Ball Wear (ASTM D2266)	0.65 mm
Four-Ball EP Weld Point (ASTM D2596)	200 kgf
Timken OK	45 lbs

Packaging Information

Part Number	Item Number	Unit Size	Quantity
020Z-04-IA	0102010CR	14 oz cartridge	10 per case
0203-04-IA	0102035BM	35 lb pail	
0210-04-IA	0102120KG	120 lb keg	
0240-04-IA	0102400DR	400 lb drum	

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
 Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium