



Chemola™ Desco Silicone Pak Extra

Extreme Service Injectable Packing

Chemola™ Desco Silicone Pak Extra is a synthetic silicone-graphite sealant/packing formulated for applications with extreme temperature differentials where minimal thermal expansion is required. It can be used to energize seals and repair damaged seals.

Recommended Uses

Aliphatic hydrocarbons, crude distillates, crude oil, diesel fuel, hydrocarbon liquids, LPG, sour gas, sour crude, water (not potable), steam, mild acids and caustics

Typical Characteristics

Appearance	Black
NLGI	6
Penetration (ASTM D217)	90-120
Base Oil	Silicone oil
Base Oil Viscosity	60,000 cSt at 25°C
Base Oil Pour Point	-40°F (-40°C)
Solids Content	Graphite, synthetic fibers
Specific Gravity	1.5
Density (lb/gal)	12.5
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>500°F (260°C)
Temperature Range	-70°F to 600°F (-56°C to 316°C)

Packaging Information

Part Number	Item Number	Unit Size	Quantity
4051-12-1A	0405016LT	1 1/2" x 18"	16 per box
405J-12-1A	040516JBX	"J" stick 1-3/8" x 8-1/2"	16 per box

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com

Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com

Premium